

### PRODUCT CATALOGUE



WWW.SOARINGEAGLEGRAINEQUIPMENT.COM



### DRIVE OVER CONVEYORS

# SA 20 & 30 DRIVE OVER CONVEYORS

Performance:	SA 20	SA 30
Tons per Hour	361	555
Standard Hydraulic Drive		
Gallons Per Min @ 2000PSI	20	25

Dimensions:	SA 20	SA 30
Belt Width	51 cm	76 cm
Belt Length	14.63 Meters	14.63 Meters
Conveyor Length	8.23 Meters	8.23 Meters
Spout Discharge Height	84 cm	66 cm
Total Weight	662 Kg	1125 Kg
Tire Size	18.5x10	20.5x10
Drive-Over Frame Height	6.35 cm	6.35 cm
Drive-Over Frame Width	3.2 Meters	3.2 Meters
Available 30 cm Extension	3.5 Meters	3.5 Meters
Adjustable Hopper	91.5x325 cm	117x325 cm

### Features:

Low Profile Drive-Over Frame

Automatic Emergency Shut-Off

Self Cleaning Rollers

Swinging Drive Wheel

Adjustable Hitch

Adjustable Frame

Adjustable Belt Tension







### DRIVE OVER CONVEYORS

### SA PETROL ENGINE

Performance:	SA 20
Tons per Hour	361
Kohler Petrol Engine	26.5 HP
Dimensions:	SA 20
Belt Width	51 cm
Belt Length	14.63 Meters
Conveyor Length	8.23 Meters
Spout Discharge Height	84 cm
Total Weight	662 Kg
Tire Size	18.5x10
Drive-Over Frame Height	6.35 cm
Drive-Over Frame Width	3.2 Meters
Available 30cm Extenstion	3.5 Meters
Adjustable Hopper	91.5x325 cm
Features:	
Low Profile Drive-Over Frame	
Automatic Emergency Shut-Of	ff
Self Cleaning Rollers	
Swinging Drive Wheel	
Adjustable Hitch	
Adjustable Frame	
Adjustable Belt Tension	



### DRIVE OVER CONVEYORS



## SA ELECTRIC DRIVE OVER CONVEYORS

Performance:	SA 20	SA 30
Tons per Hour	361	555
1 Phase 240V	10	HP
3 Phase 230-460V	10	HP
3 Phase 600V	10	HP

Dimensions:	SA 20	SA 30
Belt Width	51 cm	76 cm
Belt Length	14.63 Meters	14.63 Meters
Conveyor Length	8.23 Meters	8.23 Meters
Spout Discharge Height	84 cm	66 cm
Total Weight	662 Kg	1125 Kg
Tire Size	18.5x10	20.5x10
Drive-Over Frame Height	6.35 cm	6.35 cm
Drive-Over Frame Width	3.2 Meters	3.2 Meters
Available 30 cm Extension	3.5 Meters	3.5 Meters
Adjustable Hopper	91.5x325 cm	117x325 cm

# Features: Low Profile Drive-Over Frame Automatic Emergency Shut-Off Self Cleaning Rollers Swinging Drive Wheel Adjustable Hitch Adjustable Frame Adjustable Belt Tension



### ELECTRIC LEG CONVEYOR



WWW.SOARINGEAGLEGRAINEQUIPMENT.COM

# TL-10-24-52 SELF-PROPELLED TRUCK LOADER

	I	
Performance:	TL-10-24-52 Truck Loader	
Tons per Hour	333	
High Performance Hatz Diesel Engine	56 HP	
Dimensions:		
Tube Diameter	25.4 cm	
Belt Width	61 cm	
Overall Length	16.8 Meters	
Conveyor Length at 15 Degrees	15.4 Meters	
Conveyor Length at 31 Degrees	14 Meters	
Minimum Discharge Height	3.3 Meters	
Maximum Discharge Height	7.3 Meters	
Features:		
Self Propelled		
Ride Along Platform		
High Performance Hatz Diesel Engine		
Includes Engine and Hopper Covers		
Canola Certified		







### UB 20 & 30 TRUCK LOADERS

HYDRAULIC OR ELECTRIC DRIVE OPTIONS

UB20		UB30	
Specifications:		Specifications:	
Belt Width:	51 cm	Belt Width:	76.2 cm
Capacity:	277 Tons per Hour	Capacity:	555 Tons per Hour
Overall Length:	12.8 Meters	Overall Length:	12.8 Meters
Hopper Dimensions:	76 cm Wide x 145 cm Long	Hopper Dimensions:	102 cm Wide x 145 cm Long
Tire Size:	ST225/75 R15	Tire Size:	ST225/75 R15
Features:		Features:	
3.8 cm Diameter Roller Shafts		3.8 cm Diameter Roller Shafts	
Drive Options:		Drive Options:	
10 HP Electric Motor	3 Phase 230V	15 HP Electric Motor	3 Phase 230V
10 HP Electric Motor	3 Phase 460V	15 HP Electric Motor	3 Phase 460V
10 HP Electric Motor	3 Phase 575V	15 HP Electric Motor	3 Phase 575V
10 HP Electric Motor	1 Phase 230V	12.5 HP Electric Motor	1 Phase 230V
Hydraulic Drive		Hydraulic Drive	



### UB 20 BEAVER TAIL TRUCK LOADER

HYDRAULIC OR ELECTRIC DRIVE OPTIONS

UB20BT		
Specifications:		
Belt Width:	51 cm	
Capacity:	277 Tons per Hour	
Overall Length:	12.8 Meters	
Hopper Dimensions:	76 cm Wide x 145 cm Long	
Tire Size:	ST225/75 R15	
Features:		
3.8 cm Diameter Roller Shafts		
Collapsible Hopper		
Drive Options:		
10 HP Electric Motor	3 Phase 230V	
10 HP Electric Motor	3 Phase 460V	
10 HP Electric Motor	3 Phase 575V	
10 HP Electric Motor	1 Phase 230V	
Hydraulic Drive		



### UB 30 BEAVER TAIL TRUCK LOADER

HYDRAULIC OR ELECTRIC DRIVE OPTIONS

UB30BT		
Specifications:		
Belt Width:	76.2 cm	
Capacity:	555 Tons per Hour	
Overall Length:	12.8 Meters	
Hopper Dimensions:	102 cm Wide x 145 cm Long	
Tire Size:	ST225/75 R15	
Features:		
3.8 cm Diameter Roller Shafts		
Collapsible Hopper		
Drive Options:		
15 HP Electric Motor	3 Phase 230V	
15 HP Electric Motor	3 Phase 460V	
15 HP Electric Motor	3 Phase 575V	
12.5 HP Electric Motor	1 Phase 230V	
Hydraulic Drive		



# TRUCK LOADER CONVEYORS UB 20 BEAVER TAIL PETROL TRUCK LOADER

PETROL OVER HYDRAULIC DRIVE

UB20BT Petrol	
Specifications:	
Belt Width:	51 cm
Capacity:	277 Tons per Hour
Overall Length:	12.8 Meters
Hopper Dimensions:	76 cm Wide x 145 cm Long
Kohler Petrol Engine	26.5 HP
Features:	
3.8 cm Diameter Roller Shafts	
Self Propelled with petrol over hydraulic drive	
Hydraulic Conveyor Lift and Adjustment	



### UB 12, 15 AND 20 UNDER BIN CONVEYORS

UB 12 Under Bin Conveyor		
Features:	Performance:	
30.5 cm Chevron Belt	82 Tons per Hour	
End Drive Section	5-20 HP Electric Motor	
Mid-Drive Section	Available in Lengths From 3.6-36.5 Meters	
UB 15 Under Bin Conveyor		
Features:	Performance:	
30.5 cm Chevron Belt	164 Tons per Hour	
End Drive Section	5-20 HP Electric Motor	
Mid-Drive Section	Available in Lengths From 3.6-36.5 Meters	
UB 20 Under Bin Conveyor		
Features:	Performance:	
30.5 cm Chevron Belt	218 Tons per Hour	
End Drive Section	10-20 HP Electric Motor	
Mid-Drive Section	Available in Lengths From 3.6-36.5 Meters	









#### IMPORTED & DISTRIBUTED BY:

Wahroonga Enterprises Pty Ltd 4533 Wimmera Hwy, Marnoo Vic 3387 Ph. 03 5359 2322

www.wemachinery.com.au